



## **Technical Specification**

### **MEF 13**

# **User Network Interface (UNI) Type 1 Implementation Agreement**

**November, 2005**

## Disclaimer

The information in this publication is freely available for reproduction and use by any recipient and is believed to be accurate as of its publication date. Such information is subject to change without notice and the Metro Ethernet Forum (MEF) is not responsible for any errors. The MEF does not assume responsibility to update or correct any information in this publication. No representation or warranty, expressed or implied, is made by the MEF concerning the completeness, accuracy, or applicability of any information contained herein and no liability of any kind shall be assumed by the MEF as a result of reliance upon such information.

The information contained herein is intended to be used without modification by the recipient or user of this document. The MEF is not responsible or liable for any modifications to this document made by any other party.

The receipt or any use of this document or its contents does not in any way create, by implication or otherwise:

- (a) any express or implied license or right to or under any patent, copyright, trademark or trade secret rights held or claimed by any MEF member company which are or may be associated with the ideas, techniques, concepts or expressions contained herein; nor
- (b) any warranty or representation that any MEF member companies will announce any product(s) and/or service(s) related thereto, or if such announcements are made, that such announced product(s) and/or service(s) embody any or all of the ideas, technologies, or concepts contained herein; nor
- (c) any form of relationship between any MEF member companies and the recipient or user of this document.

Implementation or use of specific Metro Ethernet standards or recommendations and MEF specifications will be voluntary, and no company shall be obliged to implement them by virtue of participation in the Metro Ethernet Forum. The MEF is a non-profit international organization accelerating industry cooperation on Metro Ethernet technology. The MEF does not, expressly or otherwise, endorse or promote any specific products or services.

© The Metro Ethernet Forum 2005. All Rights Reserved.

# Table of Contents

<b>1.</b>	<b>Abstract.....</b>	<b>1</b>
<b>2.</b>	<b>Terminology.....</b>	<b>1</b>
<b>3.</b>	<b>Scope.....</b>	<b>2</b>
3.1	Purpose .....	2
3.2	UNI Modes .....	2
3.2.1	Type 1 – Manual Configuration .....	2
3.2.2	Type 2 – Static Service Discovery .....	2
<b>4.</b>	<b>Compliance Levels .....</b>	<b>2</b>
<b>5.</b>	<b>Common Characteristics.....</b>	<b>3</b>
5.1	Physical Medium .....	3
5.2	Ethernet Frame Format.....	3
<b>6.</b>	<b>Service Specific Characteristics.....</b>	<b>4</b>
6.1	UNI Type 1.1 .....	4
6.1.1	CE-VLAN ID .....	4
6.1.2	CE-VLAN ID/EVC Map.....	4
6.1.3	Traffic Management.....	4
6.1.4	L2 Control Processing.....	5
6.1.5	EVC Type.....	5
6.1.6	CE-VLAN ID Processing.....	5
6.1.7	CE-VLAN CoS Preservation .....	5
6.1.8	Service Frame Delivery.....	5
6.2	UNI Type 1.2.....	6
6.2.1	Service Multiplexing .....	6
6.2.2	CE-VLAN ID .....	6
6.2.3	CE-VLAN ID/EVC Map.....	6
6.2.4	Bundling.....	6
6.2.5	Traffic Management.....	6
6.2.6	L2 Control Processing.....	7
6.2.7	EVC Type.....	8
6.2.8	CE-VLAN ID Processing.....	8
6.2.9	CE-VLAN CoS Preservation .....	8
6.2.10	Service Frame Delivery.....	8
<b>7.</b>	<b>References.....</b>	<b>9</b>

## 1. Abstract

This document specifies an implementation agreement for MEF User to Network Interface (UNI) Type 1. The main objective of this version is to specify the MEF UNI characteristics and operation in manual configuration mode. This allows existing Ethernet devices (switch, router, workstation, etc) acting as CEs to be instantly compliant to this IA with no additional software or hardware upgrades. The main functionality of this version is to allow data-plane Ethernet connectivity between the UNI-C and UNI-N. This document references MEF UNI Requirements and Framework [4] for all concepts, constructs and terminology. The UNI Type 1 mode provides bare minimum data-plane connectivity services with no control-plane or management-plane capabilities..

## 2. Terminology

Term	Definition
<b>CE-VLAN CoS</b>	The user-priority bits of the IEEE 802.1Q Tag in a tagged Service Frame over UNI.
<b>CE-VLAN ID</b>	The identifier derivable from the content of a Service Frame that allows the Service Frame to be associated with an EVC at the UNI.
<b>CBS</b>	Committed Burst Size
<b>CIR</b>	committed Information Rate
<b>EVC</b>	Ethernet Virtual Connection. An association of two or more UNIs that limits the exchange of frames to UNIs in the Ethernet Virtual Connection
<b>Frame</b>	Short for Ethernet frame.
<b>Ingress</b>	The direction from the CE into the Service Provider network.
<b>Layer 2 Control Protocol Service Frame</b>	A Service Frame that is used for Layer 2 control, e.g., Spanning Tree Protocol.
<b>Multicast Service Frame</b>	A Service Frame that has a multicast destination MAC address.
<b>Multipoint EVC</b>	An EVC with two or more UNIs.
<b>EBS</b>	Excess Burst Size
<b>EIR</b>	Excess Information Rate
<b>Point-to-Point EVC</b>	An EVC with exactly 2 UNIs.
<b>Service Frame</b>	An Ethernet frame transmitted across the UNI toward the Service Provider or an Ethernet frame transmitted across the UNI toward the Subscriber.
<b>Service Multiplexing</b>	A UNI attribute in which the UNI can be in more than one EVC instance.
<b>Service Provider</b>	The organization providing Ethernet Service(s).
<b>Subscriber</b>	The organization purchasing and/or using Ethernet Services.
<b>UNI</b>	User Network Interface. The physical demarcation point between the responsibility of the Service Provider and the responsibility of the Subscriber
<b>Unicast Service Frame</b>	A Service Frame that has a unicast destination MAC address.

### **3. Scope**

#### **3.1 Purpose**

The purpose of this document is an Implementation Agreement for a manually configured Ethernet UNI. This document is based on the MEF UNI Framework [4].

#### **3.2 UNI Modes**

##### **3.2.1 Type 1 – Manual Configuration**

The manual configuration mode provides data-plane connectivity services with no control-plane and management plane capability. The scope of this Implementation Agreement is UNI Type 1.

##### **3.2.2 Type 2 – Static Service Discovery**

This mode is out of the scope of this implementation agreement

### **4. Compliance Levels**

The key words "**MUST**", "**MUST NOT**", "**REQUIRED**", "**SHALL**", "**SHALL NOT**", "**SHOULD**", "**SHOULD NOT**", "**RECOMMENDED**", "**MAY**", and "**OPTIONAL**" in this document are to be interpreted as described in RFC 2119. All key words must be use upper case, bold text

## 5. Common Characteristics

### 5.1 Physical Medium

1. A Type 1 UNI-C **MUST** support at least one of the following IEEE 802.3 Ethernet PHYs:
  - 10BASE-T in Full-duplex mode [1].
  - 100BASE-T including 100BASE-TX and 100BASE-FX in Full-duplex mode [1].
  - 1000BASE-X including 1000BASE-SX, 1000BASE-LX, and 1000BASE-T in Full-duplex mode [1].
  - 10GBASE-SR, 10GBASE-LX4, 10GBASE-LR, 10GBASE-ER, 10GBASE-SW, 10GBASE-LW, and 10GBASE-EW in Full-duplex mode [1].
2. A Type 1 UNI-N **MUST** support at least one of the following IEEE 802.3 Ethernet PHYs:
  - 10BASE-T in Full-duplex mode [1].
  - 100BASE-T including 100BASE-TX and 100BASE-FX in Full-duplex mode [1].
  - 1000BASE-X including 1000BASE-SX, 1000BASE-LX, and 1000BASE-T in Full-duplex mode [1].
  - 10GBASE-SR, 10GBASE-LX4, 10GBASE-LR, 10GBASE-ER, 10GBASE-SW, 10GBASE-LW, and 10GBASE-EW in Full-duplex mode [1].

### 5.2 Ethernet Frame Format

3. A Type 1 UNI-C **MUST** support transmission and reception of Untagged Ethernet frames according to IEEE 802.3-2002 [1]. In addition it **MAY** support transmission and reception of Priority-tagged and/or VLAN Tagged service frames in compliance to 802.3-2002.
4. A Type 1 UNI-N **MUST** support transmission and reception of Untagged, VLAN-tagged and Priority-tagged Ethernet frames according to IEEE 802.3-2002 [1].
5. A Type 1 UNI-C **MUST** support transmission and reception of Ethernet frames that have a minimum and maximum size as specified in IEEE 802.3-2002 [1].
6. A Type 1 UNI-N **MUST** support transmission and reception of Ethernet frames that have a minimum and maximum size as specified in IEEE 802.3-2002 [1].

## 6. Service Specific Characteristics

### 6.1 UNI Type 1.1

UNI Type 1.1 is a subset of UNI Type 1 that is meant to support non-service multiplexed UNIs, such as those required to support the EPL *service* [5].

#### 6.1.1 CE-VLAN ID

7. A Type 1.1 UNI-N **MUST** be able to accept any CE-VLAN ID received from UNI-C, meaning that it shouldn't discard any CE-VLAN ID.

#### 6.1.2 CE-VLAN ID/EVC Map

8. A Type 1.1 UNI-N **MUST** be able to support a single EVC.
9. A Type 1.1 UNI-N **MUST** be configurable to either map all CE-VLAN IDs to an EVC or don't map any CE-VLAN ID to any EVC.

Note: This requirement is needed for temporary disconnection of customer service, without tearing down the EVC.

#### 6.1.3 Traffic Management

10. A Type 1.1 UNI-N **MUST** be able to support per-UNI Ingress BW profiling based on [6].
11. A Type 1.1 UNI-C **SHOULD** be able to shape its traffic to the contracted BWP in order to receive the contracted QoS commitments.
12. A Type 1.1 UNI-N **MUST** be able to support color-blind BW profiling in which EIR=EBS=0 and CIR and CBS are non-zero.
13. A Type 1.1 UNI-N **MUST** allow configuration to modify CIR in the following granularities:
  - 1Mbps steps up to 10Mbps
  - 5 Mbps steps beyond 10Mbps and up to 100Mbps
  - 50 Mbps steps beyond 100Mbps and up to 1Gbps
  - 500 Mbps steps beyond 1Gbps
14. A Type 1.1 UNI-N **SHOULD** allow configuration to modify CIR in the following granularities:
  - 64 Kbps (DS0 rate) steps up to 1.422 Mbps (VC11 rate) or 1.932 Mbps (VC12 rate)
  - 1.422 Mbps (VC11 rate) or 1.932 Mbps (VC12 rate) steps up to 50 Mbps
  - 43.008 Mbps (VC3 rate) steps beyond 50 Mbps and up to 150 Mbps
  - 133.12 Mbps (VC4 rate) steps beyond 150 Mbps
15. A Type 1.1 UNI-N **MUST** be able to at least support CBS values that are equal to or greater than the  $8 \times \text{MTU} = 8 \times 1522 \text{ bytes} = 12176 \text{ bytes}$

#### **6.1.4 L2 Control Processing**

16. A Type 1.1 UNI-N **MUST** be able to pass the following L2 Control Protocols to the EVC:
- Spanning Tree Protocol (STP),
  - Rapid Spanning Tree Protocol (RSTP),
  - Multiple Spanning Tree Protocol (MSTP)
  - All LANs Bridge Management Group Block of Protocol
  - Generic Attribute Registration Protocol (GARP)
17. A Type 1.1 UNI-N **SHOULD** be able to pass the following L2 Control Protocols to the EVC:
- Link Aggregation Control Protocol (LACP)
  - Marker Protocol
  - Authentication (802.1x)
18. A Type 1.1 UNI-N **SHOULD** be able to discard 802.3x PAUSE frames

#### **6.1.5 EVC Type**

19. A Type 1.1 UNI-N **MUST** be able to support point-to-point EVCs.

#### **6.1.6 CE-VLAN ID Processing**

20. A Type 1.1 UNI-N **MUST** be able to support CE-VLAN ID preservation.

#### **6.1.7 CE-VLAN CoS Preservation**

21. A Type 1.1 UNI-N **MUST** be able to support CE-VLAN CoS preservation.

#### **6.1.8 Service Frame Delivery**

22. A Type 1.1 UNI-N **MUST** be able to Tunnel Unicast, Multicast and Broadcast service frames, except 802.3x PAUSE frames unconditionally.

**6.2 UNI Type 1.2**

UNI Type 1.2 is a subset of UNI Type 1 that is meant to support service multiplexed UNIs, such as those required to support the EVPL service [5].

**6.2.1 Service Multiplexing**

- 23. A Type 1.2 UNI-N **MUST** be able to support Service Multiplexing as defined in [MEF10].
- 24. A Type 1.2 UNI-N **SHOULD** at least be able to support a minimum number of EVCs as per following table.

<i>Link Speed</i>	<i>10/100 M bits/s</i>	<i>1 G bit/s</i>	<i>10 G bit/s</i>
<i>Minimum number of EVCs</i>	8	64	512

**6.2.2 CE-VLAN ID**

- 25. A Type 1.2 UNI-N **SHOULD** be able to support at least a minimum number of CE-VLAN IDs as per following table, which **SHOULD** be configurable in the range of 1-4095 [MEF10].

<i>Link Speed</i>	<i>10/100 M bits/s</i>	<i>1 G bit/s</i>	<i>10 G bit/s</i>
<i>Minimum number of CE-VLANs</i>	8	64	512

**6.2.3 CE-VLAN ID/EVC Map**

- 26. A Type 1.2 UNI-N **MUST** have a configurable CE-VLAN/EVC mapping table.
- 27. A Type 1.2 UNI-N **MUST** be able to drop the frames if a match in the CE-VLAN/EVC map table cannot be found.

**6.2.4 Bundling**

- 28. A Type 1.2 UNI-N **MUST** be able to support All-to-one bundling.

**6.2.5 Traffic Management**

- 29. A Type 1.2 UNI-N **MUST** be able to support per-UNI Ingress BW profiling [6].
- 30. A Type 1.2 UNI-N **MUST** be able support Per-EVC BW profiling [6].

31. A Type 1.2 UNI-N **SHOULD** be able to support Per-CoS BW profiling [6].

*Note 1: Multiple models of BW profile may exist at a UNI Type 1.2. However, a UNI Type 1.2 is not required to apply more than one BW profile to each service frame.*

*Note 2: Best Effort service is also considered to need CIR and CBS, in which CIR=CBS=0.*

32. A Type 1.2 UNI-C **SHOULD** be able to shape its traffic to the contracted BWP in order to received the contracted QoS commitments

33. A Type 1.2 UNI-N **MUST** be able to support color-blind BW profiling to enforce CIR, CBS, EIR and EBS.

34. A Type 1.2 UNI-N **MUST** allow configuration to modify CIR and EIR in the following granularities:

- 1Mbps steps up to 10Mbps
- 5 Mbps steps beyond 10Mbps and up to 100Mbps
- 50 Mbps steps beyond 100Mbps and up to 1Gbps
- 500 Mbps steps beyond 1Gbps

35. A Type 1.2 UNI-N **SHOULD** allow configuration to modify CIR and EIR in the following granularities:

- 64 Kbps (DS0 rate) steps up to 1.422 Mbps (VC11 rate) or 1.932 Mbps (VC12 rate)
- 1.422 Mbps (VC11 rate) or 1.932 Mbps (VC12 rate) steps up to 50 Mbps
- 43.008 Mbps (VC3 rate) steps beyond 50 Mbps and up to 150 Mbps
- 133.12 Mbps (VC4 rate) steps beyond 150 Mbps

36. A Type 1.2 UNI-N **MUST** be able to at least support CBS and EBS values that are equal or greater than  $8 \times \text{MTU} = 8 \times 1522 \text{ bytes} = 12176 \text{ bytes}$ .

### 6.2.6 L2 Control Processing

37. A Type 1.2 UNI-N **SHOULD** be able to discard the following L2 Control Protocols:

- Spanning Tree Protocol (STP),
- Rapid Spanning Tree Protocol (RSTP),
- Multiple Spanning Tree Protocol (MSTP)
- All LANs Bridge Management Group Block of Protocol
- Generic Attribute Registration Protocol (GARP)
- Link Aggregation Control Protocol (LACP)
- Marker Protocol
- Authentication (802.1x)
- 802.3x (PAUSE) frames

38. A type 1.2 UNI-N **SHOULD** not generate 802.3x (PAUSE) frames.

39. A Type 1.2 UNI-N **SHOULD** be configurable to peer the following L2 Control Protocols

- Link Aggregation Control Protocol (LACP)
- Marker Protocol
- Authentication (802.1x)

**6.2.7 EVC Type**

40. A Type 1.2 UNI-N **MUST** be able to support Point-to-point and Multipoint EVCs concurrently.

**6.2.8 CE-VLAN ID Processing**

41. A Type 1.2 UNI-N **MUST** be able to support CE-VLAN ID preservation.

**6.2.9 CE-VLAN CoS Preservation**

42. A Type 1.2 UNI-N **MUST** be able to support CE-VLAN CoS preservation.

**6.2.10 Service Frame Delivery**

43. A Type 1.2 UNI-N **MUST** be able to Tunnel Multicast and Broadcast service frames that are not listed in section 6.2.6 unconditionally.
44. A Type 1.2 UNI-N **MUST** be able to Tunnel all other Unicast service frames unconditionally

## 7. References

Reference	Reference Details
[1] IEEE 802.3	IEEE P 802.3 – 2002, <i>Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications</i> , 8 March 2002. (Normative)
[2] IEEE 802.3ae	IEEE 802.3ae-2002 Information Technology - Local & Metropolitan Area Networks - Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications - Media Access Control Parameters, Physical Layers and Management Parameters for 10 Gb/s Operation
[3] IEEE 802.1Q	<a href="#">IEEE 802.1Q, 2003 Edition</a> , IEEE Standards for Local and metropolitan area networks—Virtual Bridged Local Area Networks
[4] UNI-REQ-FRMK	Metro Ethernet Forum, MEF 11, User Network Interface (UNI) Requirements and Framework, November 2004
[5] MEF 6	Metro Ethernet Forum MEF 6, Ethernet Service Definition, June 2004.
[6] MEF 10	Metro Ethernet Forum MEF 10, Ethernet Services Attributes Phase 1, November 2004.